

Description of Acceptable Refillable Containers for BASF

2-Nov-15

For each container, obtain Manufacturer's written Closure Specifications and ensure tanks are closed according to these specifications prior to shipping.

All tank openings, except vents must be equipped with a one-way valve, tamper evident seal or both. (see 40 CFR Part 165.45 Subpart e)

All tanks must have a unique method of identification (see 40 CFR Part 165.45 Subpart d)

All Containers must meet or exceed US DOT Packing Group III specifications. (see 49 CFR 173, 178 & 180)

Product	Label EPA Registration No.	Container Size	Container Specification Description	Pump Seals
Prowl® H2O	241-148	15 gallon or greater capacity	Tanks should be constructed with Level 3 fluorinated Polyethylene, Stainless Steel material. or 1/4 inch thick polyethylene - HDPE.	EPDM
Prowl® 3.3 EC	241-337	15 gallon or greater capacity	Tanks should be constructed with Level 3 fluorinated Polyethylene or Stainless Steel material. or 1/4 inch thick polyethylene - HDPE.	Viton®
Basagranl® 5L	7969-112	15 gallon or greater capacity	Tanks must be constructed of Stainless Steel material or 1/4 inch thick polyethylene- HDPE. BASF does not recommend long term storage in polyethylene containers	Viton®
Varisto®	241-447	15 gallon or greater capacity		Viton®
Clarity®	7969-137	15 gallon or greater capacity	Tanks should be constructed with Level 3 fluorinated Polyethylene, Stainless Steel material, Caged Polyethylene IBC or 1/4 inch thick polyethylene - HDPE.	EPDM
Outlook®	7969-156	15 gallon or greater capacity		EPDM
Guardzman Max®	7969-192	15 gallon or greater capacity		EPDM
G-Max Lite™	7969-200	15 gallon or greater capacity		EPDM
Extreme®	241-405	15 gallon or greater capacity		EPDM
Verdict™	7969-279	15 gallon or greater capacity	Tanks should be constructed with Level 3 fluorinated Polyethylene, Stainless Steel material. or 1/4 inch thick polyethylene - HDPE.	Teflon® or Sanoprene™
Armezon® Pro	7969-372	15 gallon or greater capacity	Tanks should be constructed with Level 3 fluorinated Polyethylene, Stainless Steel material. or 1/4 inch thick polyethylene - HDPE.	Teflon® or Sanoprene™
Headline®	7969-186	15 gallon or greater capacity	Package into new or clean tanks that only had BASF Plant Health Products previously. Tanks should be constructed with Level 3 fluorinated Polyethylene, Stainless Steel material. or 1/4 inch thick polyethylene - HDPE. Tanks must remain dedicated.	Viton®
Headline AMP®	7969-291	15 gallon or greater capacity		EPDM
Headline SC®	7969-289	15 gallon or greater capacity		EPDM
Priaxor®	7969-311	15 gallon or greater capacity		EPDM

Armezon Pro, Prowl H2O, Prowl 3.3 EC, Basagran 5L, Varisto, Clarity, Outlook, Guardsman Max, Extreme, Priaxor, Headline, Headline AMP and Headline SC are registered trademarks of BASF Corp.

Sanoprene is a trademark of Exxon Mobile.

Teflon and Viton are registered trademarks of E. I. duPont Nemours and Company or it's affiliates

Container Examples

Container Specification Description

Containers Constructed with Level 3 fluorinated Polyethylene



Containers constructed with 1/4 inch thick polyethylene - HDPE.



Caged Polyethylene IBC



Markings

UN	31H2
Packing Group II	Y
Packing Group III	Z

